

TM-2-DH-SD0(J0) Torque Motor




Electrical specifications

Winding code : SD0	Symbol	Unit	Water cooling
Continuous torque	T_c	Nm	2394
Continuous current	I_c	A_{rms}	70.8
Stall torque	T_s	Nm	1950
Stall current	I_s	A_{rms}	56.6
Peak torque(for 1sec.)	T_p	Nm	4788
Peak current(for 1sec.)	I_p	A_{rms}	212
Torque constant	K_t	Nm/Arms	34.47
Electrical time constant	T_e	ms	5.9
Resistance (line to line at 25°C)	R_{25}	Ω	1.1
Inductance (line to line)	L	mH	6.5
Number of poles	2p		88
Back emf constant (line to line)	K_v	Vrms/rad/s	19.9
Motor constant (at 25°C)	K_m	Nm/ $\sqrt{W}$	26.82
Thermal resistance	R_{th}	K/W	0.013
Thermal sensor			PTC 100+PTC 130+Pt1000
Max. DC BUS		V_{DC}	750
Inertia of rotor	J	kgm^2	0.91
Thermal time constant	T_{th}	s	130
Max. continuous power dissipation	P_c	W	11654
Max. peak power dissipation	P_p	W	104494
Rated speed(at 600VDC)		rpm	121

Mechanical specifications

	Symbol	Unit	Water cooling
Mass of rotor	M_r	kg	26.9
Mass of stator	M_s	kg	101.6
Height of stator	H_s	mm	210
Height of rotor	H_r	mm	171
Length of rotor centring fit	H	mm	15
Water temperture difference for P_c	$\Delta\theta$	K	5
Minimum water flow	q	l/min	33.4
Max. pressure drop	Δp	bar	3

T-N curve



Except dimensions, all the specifications in the table are in $\pm 10\%$ of tolerance

Version: 2.00

This drawing is only for reference, detail dimensions please refer to approval drawing.

Date: 2023/6/8